

# SPK-OCA504-2x30 Watt Powered On-Wall Speaker System

The SPK-OCA504 is a powered two-way speaker system designed for indoor wall mounting. The system accepts a line-level stereo input and amplifies it using a built-in amplifier and outputs a speaker signal to the passive speaker.



## SPK-OCA504 FEATURES

---

- **Active Loudspeaker** - Stereo 2x30W amplifier and volume control.
- **Inputs** - Line-level unbalanced stereo audio on RCA connectors and a 3.5mm mini jack, balanced stereo audio on a terminal block connector.
- **Outputs** - Speaker output to passive speaker, sub-woofer, looping output for chaining to other speaker pairs.
- **Audio Level Controls** - Volume, treble and bass.
- **Magnetically Shielded.**
- **Enhanced Bass Reflex.**
- **Auto Power** - Shuts off when system is not in use, indicated by a LED.
- **Automatic Input Voltage Selector** - 90 to 240V AC, 50 to 60Hz.
- **Indoor Wall Mounting.**
- **Available in Black or White.**
- **Weight Per Single Speaker** - Active speaker 3.57kg (7.87lbs) approx., passive speaker 2.53kg (5.58lbs) approx.
- **Package** - 1 pair of U-shaped rotating mounting brackets with 4 mounting bracket screws, 1.8m power cord, 4m loudspeaker cable and a 2m RCA cable.

## SPK-OCA504 TECHNICAL SPECIFICATIONS

---

- **INPUT:**1 line level unbalanced stereo audio on a 3.5mm mini connector, 1 line level balanced stereo audio on a terminal block connector, 1 line level unbalanced stereo audio on left and right RCA connectors.
- **OUTPUTS:**1 speaker (to connect to the external passive speaker), 1 active sub-woofer on a 3.5mm mini connector, 1 looping output on a 3.5mm mini connector.
- **SPEAKER TYPE:**Two-way bass reflex, on-wall speaker.
- **WOOFER:**5.25" (133mm) polypropylene cone/rubber surround.
- **TWEETER:**0.51" (13mm) Mylar tweeter.
- **FREQUENCY RESPONSE:**45Hz to 20kHz @-10dB.
- **IMPEDANCE:**4Ω.
- **MAX. SPL:**110dB.
- **BUILT-IN POWER AMPLIFIER:**2x30W RMS.
- **CONTROL:**Volume, bass and treble control.

- **POWER SUPPLY:**90–240V AC self adjusting.
- **STANDBY MODE POWER CONSUMPTION:**0.7W.
- **MATERIALS:**Frame, grill and brackets steel; cabinet ABS.
- **INSTALLATION CLEARANCE:**22cm (8.7in) front panel to wall (with mounting bracket), 4.5cm (1.8in) back panel to wall (with mounting bracket).
- **DIMENSIONS:**18.3cm x 17cm x 24.4cm (7.2" x 6.7" x 9.6") W, D, H.
- **DIMENSIONS WITH MOUNTING BRACKET:**18.3cm x 17.2cm x 26.5cm (7.2" x 6.8" x 10.43") W, D, H.
- **ACCESSORIES:**1 pair of U-shaped rotating mounting brackets with 4 mounting bracket screws, 1.8m (5.9ft) power cord, 4m (13.1ft) loudspeaker cable and a 2m (6.6ft) RCA cable.
- **WEIGHT:**Active speaker 2.7kg (5.9lbs) approx; passive speaker 2.2kg (4.8lbs) approx.
- **WEIGHT WITH MOUNTING KIT:**Active speaker 3.1kg (6.8lbs) approx; passive speaker 2.6kg (5.7lbs) approx.